

VIBER X+



The VIBER X+TM is a digital vibration instrument designed to be easy to use and reliable for both beginners and professionals. It ensures durability and consistent performance.

The VIBER X+TM measures total vibration across selected frequency ranges and evaluates bearing conditions.

- Multiple frequency range options available, up to 16,000Hz
- Wide vibration level range, maximum of 80g peak
- Icon-oriented menus on a clear 1.8-inch display
- Operating system with numerous pre-installed languages
- Update function for the latest firmware
- 12 hours of usage on a single charge
- Battery charging via USB-C
- Rugged IP65-rated enclosure



Digital	ADC	16 bit
	Dynamic range	96 dB
	Memory	4MB
Display	Size	1.8 inch, 128x128 pixels
Signal input	AC inputs	All standard ICP accelerometers (4mA/24V)
Measurements	Frequency range total value	2 to 12800 Hz
	Frequency range BC	500 to 16000 Hz
	Amplitude range	Up to 80 g, peak
	Accuracy	$0.01~\text{g} \pm 2~\%$ for non integrated $0.1~\text{mm/s} \pm 3~\%$ for single integrated
	Resolution	Up to 0.25 Hz/line
Power	Battery	3.7 V, 2.4 Ah Li-ion
	Operating time	16 hours typical use
	Charging	4h fully charged, 2h up to 70%
	Charger	5 - 12 VDC, 10W, USB-C
Temp.	Operating Storage	-20 °C to +70 °C (-4 °F to 158 °F) -30 °C to +80 °C (-22 °F to 176 °F)
Size	Dimensions Weight	115 x 65 x 40 mm 170 gr

Version: 1.0.0 En

The following items are included:

VIBER X+

Accelerometer with one meter detachable cable Multi-plug QC 3.0 fast charger with USB-C cable

Soft bag with shoulder strap

Printed user manual

Traceable calibration certificate

Authorised Distributor in INDIA:

VIBROTECH TRAINERS & CONSULTANTS PVT LTD.,

(An ISO 9001:2015, ISO 45001:2018 Certified Company)

B2B, BBCL Sukhin, H – 29/30, South Avenue, Kamaraj Nagar, Thiruvanmiyur, Chennai -600041, INDIA Phone: 044 – 24486363 Mobile: +91 94440 43414

E-Mail : services@vibrotech.co.in, vibrotechchennai@yahoo.com

Web site: www.vibrotech.co.in